

S-Band Radar 50Ω Transistor

Part number IGT2735M30 is a high power transistor which is internally matched to 50 ohms. It is designed for S-Band radar applications and operates over the instantaneous bandwidth of 2.7 – 3.5 GHz. It utilizes gold metal gallium nitride (GaN) high electron mobility transistor (HEMT) technology operating in common source configuration. Under 300us / 10% pulse conditions it supplies a minimum of 30 watts of peak output power with 11dB gain typically. Specified operation is with Class AB bias. All devices are 100% screened for large signal RF parameters in a fixed tuned broadband matching circuit / test fixture. The use of external tuners is not allowed during screening. This device is rated for a peak output power level of $P_{PEAK} = 30W$ @ 10% duty factor. This corresponds to an average power $P_{AVG} = 3.0W$.



50 Ohm Matched

- Requires no external impedance matching circuitry

GaN on Silicon Carbide FET

- High Power Gain
- Excellent thermal stability

Depletion Mode Device

- Negative Gate Voltage to Bias
- Bias Sequencing Required
- See App Note to Prevent Damage

Gold Metal System

- Complete Gold System
- Gold Bond Wires
- Gold Package Metal
- Maximum Reliability

BeO Free Package

- Metal Based
- Epoxy Seal

High Power 50Ω RF Test / Fixture


- Broadband
- Long-term Correlation
- 100% Device RF Screening
- No External Tuning Allowed

Patent Issued


- US 8,299,857 B2

SAMPLE RF DATA

Power Output = 30 Watts



Power Output = Saturated



MAXIMUM RATINGS

Screen	Parameter	Symbol	Min	Max	Units	Test Conditions
BD	Drain-Source Breakdown Voltage	V_{DS-BK}	--	80	V	--
BD	Drain-Source Voltage	V_{DS}	--	40	V	--
BD	Gate-Source Voltage	V_{GS}	-10	0	V	--
BD	Storage Temperature Range	T_{STG}	-55	+150	°C	--
BD	Operating Junction Temperature Range	T_J	-55	+200	°C	--
BD	CW Operation	--	--	--	--	Not rated for CW operation.
Note	Screen 'BD' = parameter qualified By Design.					

THERMAL CHARACTERISTICS

Screen	Parameter	Symbol	Min	Max	Units	Test Conditions
BD	Thermal Resistance	$R_{TH(JC)}$	--	2.5	°C/W	$V_{DD}=V1, I_{DQ}=I_{DQ1}, PW=PW1, DF=DF1, T_F=25\pm5^\circ C, P_{OUT}=30W$
Note	Screen 'BD' = parameter qualified By Design.					

PROCESSING SPECIFICATIONS

Screen	Parameter	Symbol	Min	Max	Units	Test Conditions
100%	DC Wafer Probe	--	--	--	--	Per Integra specification.
Q1	Wafer DC and RF Qualification	--	--	--	--	Per Integra specification.
LM	Wire Bond Strength	--	--	--	--	Line monitor per Integra specification.
100%	Pre-cap visual inspection	--	--	--	--	Per Integra specification
100%	Gross leak test	--	--	--	--	MIL-STD-750D, Method 1071.6, Test Condition C
Note	Screen 'Q1' = parameter is qualified by assembly and test of 3 pieces minimum per wafer.					
Note	Screen 'LM' = parameter is qualified by assembly line monitor.					


DC ELECTRICAL CHARACTERISTICS

Screen	Parameter	Symbol	Min	Typ	Max	Units	Test Conditions
100%	Drain Leakage Current	I_{D-OFF}	--	0.2*	--	mA	$V_{GS} = -8V, V_{DS} = 32V, T_F = 25\pm5^\circ C, *$ Typical Only.
100%	Gate Threshold Voltage	V_{GS-TH}	--	-3.5*	--	V	$V_{DS} = 32V, I_D = 40mA, T_F = 25\pm5^\circ C, *$ Typical Only.


RF ELECTRICAL CHARACTERISTICS

Screen	Parameter	Symbol	Min	Typ	Max	Units	Test Conditions
100%	Input Return Loss	IRL	-18	-10	-5	dB	$V_{DD}=V1, I_{DQ}=I_{DQ1}, PW=PW1, DF=DF1, T_F=T_{F1}, P_{OUT}=P_{OUT1}, F=F1, F2, F3.$
100%	Power Gain	Gp	10.0	11.0	13.0	dB	$V_{DD}=V1, I_{DQ}=I_{DQ1}, PW=PW1, DF=DF1, T_F=T_{F1}, P_{OUT}=P_{OUT1}, F=F1, F2, F3.$
100%	Drain Efficiency	η_D	45	50	75	%	$V_{DD}=V1, I_{DQ}=I_{DQ1}, PW=PW1, DF=DF1, T_F=T_{F1}, P_{OUT}=P_{OUT1}, F=F1, F2, F3.$
100%	Pulse Amplitude Droop	D	-0.50	-0.10	0.30	dB	$V_{DD}=V1, I_{DQ}=I_{DQ1}, PW=PW1, DF=DF1, T_F=T_{F1}, P_{OUT}=P_{OUT1}, F=F1, F2, F3.$
100%	Delta Insertion Phase	DIP	-30	--	+30	DEG	$V_{DD}=V1, I_{DQ}=I_{DQ1}, PW=PW1, DF=DF1, T_F=T_{F1}, P_{OUT}=P_{OUT1}, F=F3.$
100%	3:1 Load Mismatch Stability	VSWR-S	3:1		--	--	$V_{DD}=V1, I_{DQ}=I_{DQ1}, PW=PW1, DF=DF1, T_F=T_{F1}, P_{OUT}=P_{OUT1}, F=F1, F2, F3.$ Rotate 3:1 output VSWR through 360° phase. No oscillatory or pulse break-up characteristics allowed on detected output pulse. All non-harmonically related signals must be at least -65 dBc.
Note 1	$V1 = 32V; I_{DQ1} = 40mA; PW1 = 300\mu s; DF1 = 10\%, P_{OUT1} = 30W.$						
Note 2	Test Frequencies: F1 = 2.7 GHz, F2 = 3.1 GHz, F3 = 3.5 GHz.						
Note 3	$T_{F1} = 30\pm 5^\circ C$ = Device flange temperature.						
Note 4	Screen 'BD' = parameter qualified By Design.						

PACKAGE DIMENSIONAL OUTLINE DRAWING



RF TEST FIXTURE



CONTACT FACTORY FOR RF TEST FIXTURE CAD DRAWING WITH CIRCUIT DIMENSIONS

DEFINITIONS

Data Sheet Status	
Proposed Specification	This data sheet contains proposed specifications.
Preliminary Specification	This data sheet contains specifications based on preliminary measurements and data.
Product Specification	This data sheet contains final product specifications.
Maximum Ratings	
Stress above one or more of the maximum ratings may cause permanent damage to the device. These are maximum ratings only operation of the device at these or at any other conditions above those given in the characteristics sections of the specification is not implied. Exposure to maximum values for extended periods of time may affect device reliability.	

DISCLAIMER

Integra Technologies Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Integra Technologies Inc. assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Integra Technologies Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Integra Technologies Inc. customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Integra Technologies Inc. for any damages resulting from such improper use or sale.