


Part Number: **ILD1214EL200**

L-Band RF Power LDMOS Transistor

The high power pulsed transistor part number ILD1214EL200 is designed for L-Band systems operating at 1.215–1.400 GHz. Operating at a pulse width of 5ms with a duty factor of 20%, this dual LDMOS device supplies a minimum of 200 watts of peak pulse power across the instantaneous operating bandwidth of 1.215–1.400 GHz. Fabricated with all gold metal contact, wire bonding and package for maximum reliability. All devices are 100% screened for large signal RF parameters in the broadband RF test fixture across the entire specified operating bandwidth with no variable or external tuning.



TYPICAL BROADBAND DATA

Device	Freq (MHz)	Pi (W)	I _d (A)	RL (dB)	P _o (W)	η _d (%)	G (dB)	dG (dB)	Drp (dB)	VSWR 2:1
D4474-1	1215	10.9	14.76	-18	200	45.2	12.64		-0.02	S P
	1300	11	15.8	-18	200	42.2	12.60	0.56	-0.11	S P
	1400	12.4	15	-16	200	44.4	12.08		-0.13	S P

Integra

TECHNOLOGIES, INC.

Silicon LDMOS

- High Power Gain
- Superior Thermal Stability

Class AB Operation

- Gate biased to I_{DQ}=2x250mA

Configuration

- Common Source

Gold Metal

- Gold Chip Metal
- Gold Wire Bond
- Maximum Reliability

Package

- Thermally Enhanced
- Gold Metal Based

Epoxy Sealed Lid

- Gross Leak Qualified

RF Test Fixture

- Broadband
- Matched to 50Ω
- Long-term Correlation
- 100% Device RF Screening
- No External Tuning required

MAXIMUM RATINGS

Screen	Parameter	Symbol	Min	Max	Units	Test Conditions
BD	Drain-Source Voltage	V_{DS}	--	65	V	--
BD	Gate-Source Voltage	V_{GS}	-0.5	+12	V	--
BD	Storage Temperature Range	T_{STG}	-40	+150	°C	--
BD	Operating Junction Temperature Range	T_J	-55	+200	°C	--
Note	Screen 'BD' = parameter qualified By Design.					

THERMAL CHARACTERISTICS

Screen	Parameter	Symbol	Min	Max	Units	Test Conditions
BD	Thermal Resistance	$R_{TH(JC)}$	--	0.25	°C/W	$V_{dd}=30V, I_{DQ}=2x250mA, T_F=70\pm5^\circ C, P_{OUT}=200W$
Note	Screen 'BD' = parameter qualified By Design.					

PROCESSING SPECIFICATIONS

Screen	Parameter	Symbol	Min	Max	Units	Test Conditions
100%	DC Wafer Probe	--	--	--	--	Per Integra specification.
Q1	Wafer DC and RF Qualification	--	--	--	--	Per Integra specification.
LM	Wire Bond Strength	--	--	--	--	Line monitor per Integra specification.
100%	Pre-cap visual inspection	--	--	--	--	Per Integra specification
100%	Gross leak test	--	--	--	--	MIL-STD-750D, Method 1071, Test Condition C
Note	Screen 'Q1' = parameter is qualified by assembly and test of 3 pieces minimum per wafer.					
Note	Screen 'LM' = parameter is qualified by assembly line monitor.					

DC ELECTRICAL CHARACTERISTICS

Screen	Parameter	Symbol	Min	Max	Units	Test Conditions
100%	Drain-Source Breakdown Voltage (each side)	BV_{DSS}	65	--	V	$I_D = 40mA, V_{GS} = 0V, T_F = 30\pm5^\circ C$
100%	Drain Leakage Current (each side)	I_{DSS}	--	10	μA	$V_{DS} = 30V, V_{GS} = 0V, T_F = 30\pm5^\circ C$
100%	Gate Threshold Voltage (each side)	V_{GSTH2}	1.5	2.5	V	$I_D = 100mA, V_{DS} = 5V, T_F = 30\pm5^\circ C$
100%	Gate Leakage Current (each side)	I_{GSS}	--	1.0	μA	$V_{GS} = 5V, V_{DS} = 0V, T_F = 30\pm5^\circ C$

RF ELECTRICAL CHARACTERISTICS

Screen	Parameter	Symbol	Min	Max	Units	Test Conditions
100%	Input Return Loss	RL	-18	-7	dB	$V_{DD}=V1$; $I_{DQ}=I_{DQ1}$; $T_F=T_{F1}$; $P_O=P_{OUT1}$; $F=F1, F2, F3$; PW1,DF1
100%	Power Gain	G_P	10	16.5	dB	$V_{DD}=V1$; $I_{DQ}=I_{DQ1}$; $T_F=T_{F1}$; $P_O=P_{OUT1}$; $F=F1, F2, F3$; PW1,DF1
100%	Input Power	P_i	4.5	20.0	W	$V_{DD}=V1$; $I_{DQ}=I_{DQ1}$; $T_F=T_{F1}$; $P_O=P_{OUT1}$; $F=F1, F2, F3$; PW1,DF1
100%	Drain Current Efficiency	η_D	38	75	%	$V_{DD}=V1$; $I_{DQ}=I_{DQ1}$; $T_F=T_{F1}$; $P_O=P_{OUT1}$; $F=F1, F2, F3$; PW1,DF1
100%	Pulse Amplitude Droop	Droop	-0.5	0.5	dB	$V_{DD}=V1$; $I_{DQ}=I_{DQ1}$; $T_F=T_{F1}$; $P_O=P_{OUT1}$; $F=F1, F2, F3$; PW1,DF1
100%	Gain Flatness versus Frequency	GF	0	2.0	dB	$V_{DD}=V1$; $I_{DQ}=I_{DQ1}$; $T_F=T_{F1}$; $P_O=P_{OUT1}$; $F=F1, F2, F3$; PW1,DF1
100%	Stability into 2:1 VSWR	VSWR-S	2:1	--	--	$V_{DD}=V1$; $I_{DQ}=I_{DQ1}$; $T_F=T_{F1}$; $P_O=P_{OUT1}$; $F=F1, F2, F3$; PW1,DF1 Rotate 2:1 output VSWR through 360° phase. No oscillatory or pulse break-up characteristics allowed on detected output pulse.
Note 1	V1=30V; I_{DQ1} (Drain Quiescent Current)=250mA/side					
Note 2	PW1(Pulse Width 1) =5ms; DF1(Duty Factor 1)=20%;					
Note 3	Output Power Test Level: $P_{OUT1}=200W$					
Note 4	Test Frequencies: F1=1.215GHz, F2=1.300GHz, F3=1.400GHz					
Note 5	Device Temperature Flange: T_{F1} (Flange Temp)=30±5°C					
Note 6	RF Electrical characteristics are tested in broadband RF test fixture. Thermal grease is applied to the flange for RF testing.					


BROADBAND RF TEST FIXTURE IMPEDANCE CHARACTERISTICS

Frequency (GHz)	Z_{IF} (Ω)	Z_{OF} (Ω)
1.215	1.8 -j1.2	1.2 -j2.9
1.300	1.7 -j0.4	1.2 -j2.1
1.400	1.6 +j0.6	1.2 -j1.4

Z_{IF} = The test fixture input impedance for each side.

Z_{OF} = The test fixture output impedance for each side.


PACKAGE DIMENSIONAL OUTLINE DRAWING



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.615	1.625	41.02	41.27
B	1.395	1.405	35.43	35.69
C	0.634	0.674	16.10	17.12
D	0.395	0.405	10.03	10.29
E	1.219	1.241	30.96	31.52
F	0.455	0.465	11.56	11.81
G	0.075	0.085	1.90	2.16
H	0.120	0.130	3.05	3.30
J	0.535	0.545	13.59	13.84
K	0.059	0.069	1.499	1.753
L	0.081	0.091	2.06	2.31
M	0.164	0.194	4.16	4.93
N	0.004	0.007	0.10	0.18
□	0.354	0.364	8.99	9.24

PIN SCHEDULE	
1	SOURCE
2	GATE
3	DRAIN

RF-TEST-FIXTURE ASSEMBLY AND PART LIST



CONTACT FACTORY FOR RF TEST FIXTURE CAD DRAWING WITH CIRCUIT DIMENSIONS

DEFINITIONS

ILD1214EL200 PRODUCT SPECIFICATION
FILE: ILD1214EL200-REV-NC-DS-REV-D
Page 5 of 6

www.integrattech.com
PHONE: 310-606-0855
FAX: 310-606-0865

INTEGRA TECHNOLOGIES, INC.
321 CORAL CIRCLE
EL SEGUNDO, CA 90245-4620

Data Sheet Status	
Proposed Specification	This data sheet contains proposed specifications.
Preliminary Specification	This data sheet contains specifications based on preliminary measurements and data.
Product Specification	This data sheet contains final product specifications.
Maximum Ratings	
Stress above one or more of the maximum ratings may cause permanent damage to the device. These are maximum ratings only. Operation of the device at these or at any other conditions above those given in the characteristics sections of the specification is not implied. Exposure to maximum values for extended periods of time may affect device reliability.	

DISCLAIMER

Integra Technologies Inc. reserves the right to make changes without further notice to any products herein. Integra Technologies Inc. makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Integra Technologies Inc. assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Integra Technologies Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Integra Technologies Inc. customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Integra Technologies Inc. for any damages resulting from such improper use or sale.